


3119A Multi-Conductor - DeviceBus® for Phoenix Contact InterBus-S®



For more Information
please call

1-800-Belden1

**General Description:**

18 and 24 AWG stranded tinned copper conductors, PVC insulation (power), PE insulation (data), overall Beldfoil® shield (100% coverage) plus a tinned copper braid (90% coverage), polyurethane jacket.

Physical Characteristics (Overall)**Conductor****AWG:**

| # Conductors | # Pairs | AWG | Stranding | Conductor Material | Dia. (mm) |
|--------------|---------|-----|-----------|--------------------|-----------|
| | 3 | 24 | 7x32 | TC - Tinned Copper | 0.610 |
| 3 | | 18 | 7x26 | TC - Tinned Copper | 1.524 |

Total Number of Conductors: 9

Insulation**Insulation Material:**

| Insulation Material | AWG |
|--------------------------|-----|
| PE - Polyethylene | 24 |
| PVC - Polyvinyl Chloride | 18 |

Outer Shield**Outer Shield Material:**

| Layer # | Outer Shield Trade Name | Type | Outer Shield Material | Coverage (%) |
|---------|-------------------------|-------|------------------------------|--------------|
| 1 | Beldfoil® | Tape | Aluminum Foil-Polyester Tape | 100 |
| 2 | | Braid | TC - Tinned Copper | 90 |

Outer Shield Drain Wire AWG:

| AWG | Stranding | Drain Wire Conductor Material |
|-----|-----------|-------------------------------|
| 24 | 7x32 | TC - Tinned Copper |

Outer Shield Drain Wire Diameter: .024

Outer Jacket**Outer Jacket Material:**

| Outer Jacket Material |
|-----------------------|
| PUR - Polyurethane |

Overall Cable**Overall Cabling Color Code Chart:**

| Number | Color | AWG |
|--------|---------------------|-----|
| 1 | White & Brown | 24 |
| 2 | Red | 18 |
| 3 | Pink & Gray | 24 |
| 4 | Blue | 18 |
| 5 | Yellow & Green | 24 |
| 6 | Green/Yellow Stripe | 18 |

Overall Nominal Diameter: 8.458 mm

Mechanical Characteristics (Overall)

Operating Temperature Range: -40°C To +80°C

UL Temperature Rating: 80°C (UL AWM Style 20233)

3119A Multi-Conductor - DeviceBus® for Phoenix Contact InterBus-S®

| | |
|-----------------------------------|--------------|
| Bulk Cable Weight: | 92.268 Kg/Km |
| Max. Recommended Pulling Tension: | 444.820 N |
| Min. Bend Radius/Minor Axis: | 76.200 mm |

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

| | |
|---------------------------------------|-----------------------------|
| AWM Specification: | UL Style 20233 (300 V 80°C) |
| EU CE Mark: | Yes |
| EU Directive 2000/53/EC (ELV): | Yes |
| EU Directive 2002/95/EC (RoHS): | Yes |
| EU RoHS Compliance Date (mm/dd/yyyy): | 10/01/2005 |
| EU Directive 2002/96/EC (WEEE): | Yes |
| EU Directive 2003/11/EC (BFR): | Yes |
| CA Prop 65 (CJ for Wire & Cable): | Yes |
| MII Order #39 (China RoHS): | Yes |

Suitability

| | |
|----------------------|------|
| Sunlight Resistance: | High |
|----------------------|------|

Plenum/Non-Plenum

| | |
|---------------|----|
| Plenum (Y/N): | No |
|---------------|----|

Electrical Characteristics (Overall)

Nom. Characteristic Impedance:

| Impedance (Ohm) |
|-----------------|
| 100 |

Nom. Capacitance Conductor to Shield:

| Capacitance (pF/m) |
|--------------------|
| 50.5274 |

Nominal Velocity of Propagation:

| Description | VP (%) |
|-------------|--------|
| 24 AWG | 66 |

Nom. Conductor DC Resistance:

| Description | DCR @ 20°C (Ohm/km) |
|-------------|---------------------|
| 24 | 76.7754 |
| 18 | 21.6546 |

Nominal Outer Shield DC Resistance:

| DCR @ 20°C (Ohm/km) |
|---------------------|
| 8.8587 |

Max. Operating Voltage - UL:

| Voltage |
|--------------------------------|
| 300 V RMS (UL AWM Style 20233) |

Max. Recommended Current:

| Description | Current |
|-------------|---------|
| 24 AWG | 2.1 |
| 18 AWG | 4.8 |

Notes (Overall)

Notes: Oil Resistance: High

Put Ups and Colors:

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|--------|-------|-------------|-------|-------|-----------|
|--------|-------|-------------|-------|-------|-----------|

METRIC MEASUREMENT VERSION

3119A Multi-Conductor - DeviceBus® for Phoenix Contact InterBus-S®

| | | | | | |
|---------------|--------|-----------|-----------|---|----------------------------|
| 3119A Y5P1000 | 305 MT | 32.205 KG | GREEN Y5P | C | 3PR #24 PE 3 #18 PVC SH PU |
| 3119A Y5P500 | 152 MT | 16.103 KG | GREEN Y5P | C | 3 PR#24 PE 3#18 PVC SH PU |

Notes:

C = CRATE REEL PUT-UP.

Test Reports**a) UL**

- i) UL Test Reports are available on-line through the UL Client Document Access web portal.
- ii) UL Inspection Reports are also available through the UL Client Document Access web portal.

b) CSA

- i) CSA "Descriptive Report and Test Results" documents are available on the CSA Gateway Portal.
- ii) CSA Inspection Reports are maintained on the CSA issued 'flash drive' at each manufacturing location.

* other test data may be available if requested at time of order.

Revision Number: 1 Revision Date: 04-11-2008

© 2012 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.