


7977WB Coax - Low Loss 50 Ohm Wireless RF Transmission Cable



For more Information
please call

1-800-Belden1

**General Description:**

5.5 AWG solid .176" bare copper-covered aluminum conductor, foam HDPE insulation, Duobond® II (100% coverage) plus a tinned copper braid shield (85% coverage), flooded water-resistant polyethylene jacket.

Physical Characteristics (Overall)**Conductor**

AWG:

# Coax	AWG	Stranding	Conductor Material	Dia. (mm)
1	5.5	Solid	BCCA - Bare Copper Covered Aluminum	4.4704

Total Number of Conductors: 1

Insulation

Insulation Material:

Insulation Material	Dia. (mm)
FHDPE - Foam High Density Polyethylene	11.557

Outer Shield

Outer Shield Material:

Layer #	Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
1	Bonded Duofoil®	Tape	Bonded Aluminum Foil-Polyester Tape-Aluminum Foil	100
2		Braid	TC - Tinned Copper	85

Outer Shield Flooding Grease: PO - Polyolefin

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PE - Polyethylene

Overall Cable

Overall Nominal Diameter: 14.986 mm

Mechanical Characteristics (Overall)

Operating Temperature Range:	-40°C To +80°C
Non-UL Temperature Rating:	80°C
Bulk Cable Weight:	242.577 Kg/Km
Max. Recommended Pulling Tension:	1289.978 N
Min. Bend Radius/Minor Axis:	149.860 mm

Applicable Specifications and Agency Compliance (Overall)**Applicable Standards & Environmental Programs**

EU CE Mark:	No
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2005

7977WB Coax - Low Loss 50 Ohm Wireless RF Transmission Cable

EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MIL Order #39 (China RoHS):	Yes
Series Type:	RF 600

Suitability

Suitability - Outdoor:	Yes
Suitability - Aerial:	Yes - when supported by a messenger wire
Suitability - Burial:	Yes

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Electrical Characteristics (Overall)**Nom. Characteristic Impedance:**

Impedance (Ohm)
50

Nom. Inductance:

Inductance (µH/m)
0.19686

Nom. Capacitance Conductor to Shield:

Capacitance (pF/m)
80.7126

Nominal Velocity of Propagation:

VP (%)
85

Nominal Delay:

Delay (ns/m)
3.90439

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)
1.73893

Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/km)
5.9058

Maximum VSWR:

Start Freq. (MHz)	Stop Freq. (MHz)	Max. VSWR
5.000	2690.000	1.25:1
2690.000	3290.000	2.00:1
3290.000	6000.000	1.43:1

Nom. Attenuation:

Freq. (MHz)	Attenuation (dB/100m)
30	1.50926
50	2.00141
150	3.21538
220	3.87158
450	5.64332
900	8.33374
1500	11.1554
1800	12.3694
2000	13.1568
2500	15.027
3000	16.6347

METRIC MEASUREMENT VERSION

7977WB Coax - Low Loss 50 Ohm Wireless RF Transmission Cable

3500	18.2424
4500	21.1296
5800	24.8044
6000	25.4278

Max. Power Rating:

Freq. (MHz)	Rating (W)
30	5057
220	1975
450	1353
900	921
1500	691
1800	623
2000	587
3500	425
4500	368
5800	315
6000	308

Max. Operating Voltage - Non-UL:

Voltage
300 V RMS

Notes (Overall)

Notes: 100% Sweep tested. Belden® The Wire in Wireless®

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
7977WB 0101000	305 MT	66.678 KG	BLACK	C	#5H GIPPE SH LDPE
7977WB 010500	152 MT	33.566 KG	BLACK	C	#5H GIPPE SH LDPE

Notes:

C = CRATE REEL PUT-UP.

Test Reports

a) UL

- i) UL Test Reports are available on-line through the UL Client Document Access web portal.
- ii) UL Inspection Reports are also available through the UL Client Document Access web portal.

b) CSA

- i) CSA "Descriptive Report and Test Results" documents are available on the CSA Gateway Portal.
- ii) CSA Inspection Reports are maintained on the CSA issued 'flash drive' at each manufacturing location.

* other test data may be available if requested at time of order.

Revision Number: 3 Revision Date: 02-08-2010

© 2012 Belden, Inc
 All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.