

9550 Multi-Conductor - Computer Cable for EIA RS-232 Applications



For more Information
please call

1-800-Belden1



General Description:

24 AWG stranded (7x32) TC conductors, semi-rigid PVC insulation, twisted pairs, overall Beldfoil shield (100% coverage), 24 AWG stranded TC drain Wire (continued), PVC jacket.

Physical Characteristics (Overall)

Conductor

AWG:

# Pairs	AWG	Stranding	Conductor Material
50	24	7x32	TC - Tinned Copper

Total Number of Conductors: 100

Insulation

Insulation Material:

Insulation Material	Wall Thickness (mm)
S-R PVC - Semi-Rigid Polyvinyl Chloride	0.279

Outer Shield

Outer Shield Material:

Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape w/Shorting Fold	100

Outer Shield Drain Wire AWG:

AWG	Stranding	Drain Wire Conductor Material
24	7x32	TC - Tinned Copper

Outer Jacket

Outer Jacket Material:

Outer Jacket Material	Nom. Wall Thickness (mm)
PVC - Polyvinyl Chloride	1.372

Overall Cable

Overall Nominal Diameter: 17.983 mm

Pair

Pair Color Code Chart:

Number	Color
1	Blue & White
2	Orange & White
3	Green & White
4	Brown & White
5	Gray & White
6	Blue/ White & White
7	Blue/Orange & White
8	Blue/Green & White
9	Blue/Brown & White
10	Blue/Gray & White
11	Orange/White & White
12	Orange/Green & White
13	Orange/Brown & White
14	Orange/Gray & White
15	Green/White & White

9550 Multi-Conductor - Computer Cable for EIA RS-232 Applications

16	Green/Brown & White
17	Green/Gray & White
18	Brown/White & White
19	Brown/Gray & White
20	Gray/White & White
21	Blue & Red
22	Orange & Red
23	Green & Red
24	Brown & Red
25	Gray & Red
26	Blue/White & Red
27	Blue/Orange & Red
28	Blue/Green & Red
29	Blue/Brown & Red
30	Blue/Gray & Red
31	Orange/White & Red
32	Orange/Green & Red
33	Orange/Brown & Red
34	Orange/Gray & Red
35	Green/White & Red
36	Green/Brown, Red
37	Green/Gray & Red
38	Brown/White & Red
39	Brown/Gray & Red
40	Gray/White & Red
41	Blue & Black
42	Orange & Black
43	Green & Black
44	Brown & Black
45	Gray & Black
46	Blue/White & Black
47	Blue/Orange & Black
48	Blue/Green & Black
49	Blue/Brown & Black
50	Blue/Gray & Black

Mechanical Characteristics (Overall)

Operating Temperature Range:	-30°C To +80°C
Non-UL Temperature Rating:	80°C (UL AWM Style 2464)
Bulk Cable Weight:	425.625 Kg/Km
Max. Recommended Pulling Tension:	2446.510 N
Min. Bend Radius/Minor Axis:	184.150 mm

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC/(UL) Specification:	CMG
CEC/C(UL) Specification:	CMG
AWM Specification:	UL Style 2464 (300 V 80°C)
CSA Specification:	AWM I A
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005
EU Directive 2002/96/EC (WEEE):	Yes

METRIC MEASUREMENT VERSION

9550 Multi-Conductor - Computer Cable for EIA RS-232 Applications

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS): Yes

Flame Test

UL Flame Test: UL1685 FT4 Loading

C(UL) Flame Test: FT4

Plenum/Non-Plenum

Plenum (Y/N): No

Electrical Characteristics (Overall)

Nom. Capacitance Conductor to Conductor:

Capacitance (pF/m)

98.43

Nom. Capacitance Cond. to Other Conductor & Shield:

Capacitance (pF/m)

164.05

Nominal Velocity of Propagation:

VP (%)

60

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)

78.744

Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/km)

49.8712

Max. Operating Voltage - UL:

Voltage

300 V RMS

Max. Recommended Current:

Current

1.1 Amps per conductor @ 25°C

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
9550 060100	30 MT	14.470 KG	CHROME	C	50 PR #24 PVC FS PVC
9550 0601000	305 MT	141.068 KG	CHROME	C D	50 PR #24 PVC FS PVC
9550 060500	152 MT	73.482 KG	CHROME	C D	50 PR #24 PVC FS PVC

Notes:

C = CRATE REEL PUT-UP.

D = FINAL PUT-UP LENGTH MAY VARY -0% TO +20% FROM LENGTH SHOWN.

Test Reports

a) UL

- i) UL Test Reports are available on-line through the UL Client Document Access web portal.
- ii) UL Inspection Reports are also available through the UL Client Document Access web portal.

b) CSA

- i) CSA "Descriptive Report and Test Results" documents are available on the CSA Gateway Portal.
- ii) CSA Inspection Reports are maintained on the CSA issued 'flash drive' at each manufacturing location.

* other test data may be available if requested at time of order.

Revision Number: 2 Revision Date: 08-31-2012

© 2012 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications

9550 Multi-Conductor - Computer Cable for EIA RS-232 Applications

described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.